



SECTION I: PRODUCT INFORMATION

PRODUCT: **Sika® Duochem 200**

REVISION DATE: January 31, 2013

USAGE: Diluent-solvent

MANUFACTURER/SUPPLIER: Sika Canada Inc.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9

EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666

TDG CLASSIFICATION: DIACETONE-ALCOHOL

WHMIS Classification: B3, D2B

UN NUMBER: 1148

CLASS: 3

Packaging Group: III

SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (mg/kg) (route, species)	LC ₅₀ (species, route)
DIACETONE ALCOHOL	60-100	ACGIH 50ppm (TWA)	123-42-2	4 000 (oral, rat)	NOT AVAILABLE

SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Liquid
Appearance and Odor: Clear and colorless liquid with ketone odor
Odor Threshold: 0.27 ppm
Evaporation Rate: < 1 (N-Butyl acetate=1)
Vapor Density: 4 (Air=1)
Vapor Pressure: < 1 kPa @ 55°C (calculated)

Boiling Point: 168°C
Freezing Point: - 43°C
Density: ~ 0.94 g/mL
Water Solubility: Not established
pH: Not established
% volatility: Not established
Water/Oil Distribution: Not established

PRODUCT: **Sika® Duochem 200****SECTION IV: FIRE AND EXPLOSION HAZARDS**

Flammability:	Combustible.	TDG Flammability Class:	3
If Yes, under what conditions:	Dangerous fire hazard Avoid sparks, flame or static discharge.	Flammable upper limits (% vol.):	6.9
		Flammable lower limits (% vol.):	1.8
		Flash Point (method used):	56°C (TCC)
		Auto-ignition temperature:	Not established
		Dangerous Combustion Products:	Carbon oxides.
Extinguishing methods:	Carbon Dioxide, water fog, foam or dry chemical.	Protect from mechanical impact:	No
		Protect from static discharge:	Yes
Special Methods:	Fire-fighters should wear full protective clothing including self-contained breathing apparatus since toxic gases are emitted. When heated in fire, explosive gas mixtures with air can form. Cool fire-exposed containers with water or water fog.		

SECTION V: REACTIVITY

Chemical stability:	Yes	Dangerous decomposition products:	Carbon oxides.
If not, under what conditions:	But avoid excessive heat.		
Incompatibility with other material:	Yes	Polymerization Risks:	No
If Yes, which ones:	Mineral and organic acids.		

PRODUCT: **Sika® Duochem 200****SECTION VI: TOXIC PROPERTIES**

ROUTE OF ENTRY / CONTACT

Eyes: May cause eye irritation.

Carcinogenicity: Not available

Skin: Prolonged or repeated contact may cause irritation to the skin. May cause defatting.

Toxic effects on reproduction: Not available

Inhalation: Overexposure may cause nasal and respiratory irritation.

Teratogenicity: Not available

Ingestion: May cause irritation to the G.I. system, nausea, vomiting and diarrhea. Aspiration of ingested material into lungs may cause chemical congestion which can be fatal.

Mutagenicity: Not available

Product with synergistic effects: Unknown.

May aggravate pre-existing dermatitis. May also provoke anemia.

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems. An over exposure may cause death.

PRODUCT: **Sika® Duochem 200****SECTION VII: PREVENTIVE MEASURES****PERSONAL PROTECTIVE EQUIPMENT**

Gloves: Chemical resistant gloves.

Respiratory equipment: NIOSH approved mask with organic vapor cartridge.

Eyes: Full-face mask or safety glasses

Shoes: Leather

Clothing: Rubber Apron

Other: Shower

OTHERS

Ventilation: Use adequate ventilation

Procedure in case of leaks: Remove all sources of ignition (flames, sparks, etc.). Provide adequate ventilation. Avoid prolonged breathing of vapors. Remove to a container or absorb with clay, diatomaceous earth or other suitable inert absorbent.

Handling and Equipment Methods: Avoid inhalation, skin and eye contact. Wash repeatedly with soap and water during the workday.

Warehouse Requirements: Keep all containers closed in a cool, dry and well-ventilated area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class.

Waste Disposal: Dispose of residues according to municipal, provincial or federal laws for disposal of chemicals. Do not incinerate closed containers.



PRODUCT: Sika® Duochem 200

SECTION VIII: FIRST AID

Skin: Remove contaminated clothing and shoes.
Wash immediately with plenty of soap and water.
Wash clothing before re-wearing.
Consult a physician if required.

Eyes: Rinse eyes immediately with plenty of water keeping the eyelids open in order to ensure a complete rinsing.
This should last at least 15 minutes for maximum protection.
Consult a physician immediately.

Inhalation: In the case of overexposure, evacuate to fresh air.
Consult a physician if required.

Ingestion: Drink plenty of water. Do not induce vomiting.
Do not give anything by mouth to an unconscious person.
See a physician immediately.

SECTION IX: PREPARATION INFORMATION

Prepared By: Sika Canada R & D.
Telephone #: (514) 697-2610
Fax #: (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.